



> PRINT

**ECOSYS P3055dn**

MONOCHROME PRINTER  
FOR A4 FORMAT

# THE RELIABLE PRINTING POWERHOUSE.



Product depicted includes optional paper feeder

When the going gets tough, you need a printer that exceeds all expectations to help you meet your deadline. Our ECOSYS P3055dn does exactly that. With a print speed of up to 55 pages per minute, a fast time to first print and superior 1,200 dpi resolution, it satisfies even the most demanding of workgroups. The device has enhanced security features and flexible paper handling options, with a maximum paper capacity of 2,600 sheets. And its long-life components mean incredibly low running costs and impact on the environment.

- > Up to 55 pages per minute A4 and A5
- > Time to first print: only 6.6 seconds
- > Standard Gigabit LAN, Wi-Fi option with Wi-Fi Direct available
- > Mobile Printing support for Mopria and KYOCERA Mobile Print
- > Double-sided and N-up printing for less paper consumption
- > Up to 6 paper trays for superior flexibility and high capacity
- > Optimal document distribution and workflow with Print&Follow™\*
- > Advanced document handling with optional SD cards
- > Environmentally friendly: long-life components, low energy consumption
- > Exceptionally low printing costs in its class

\* Optional



**ECOSYS** stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that toner is the only consumable for the first 500,000 pages. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.

#### Environmental print features

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode), Quiet mode (reduced print speed).

#### KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

#### ECOSYS P3055dn

##### GENERAL

**Technology:** KYOCERA ECOSYS Laser

**Control panel:** 5 line LCD back lit display with alphanumeric keypad

**Engine speed:** Up to 55 pages per minute in A4 and A5

**Resolution:** 1,200 dpi

**Duty cycle:** Max. 250,000 pages per month

**Warm-up time:** Approx. 25 seconds or less from power on

**Time to first page:** Approx. 6.6 seconds or less

**Dimensions:** (W x D x H) 380 mm x 410 mm x 320 mm, 396 mm x 421 mm x 342 mm incl. curves

**Weight:** Approx. 15.5 kg (main unit)

**Power source:** 220/240 V, 50/60 Hz

##### Power consumption

Printing: 675 W

Ready mode: 11 W

Sleep Mode: 0.9 W

##### Noise (Sound pressure level: ISO 7779/ISO 9296):

Printing: 54.7 dB(A) LpA

Quiet Mode: 50.4 dB(A) LpA

Ready mode: 27.1 dB(A) LpA

Sleep mode: Immeasurably low

##### Safety standards: TÜV-GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

#### PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

**Input capacity:** 100-sheet multi-purpose tray; 60–220 g/m<sup>2</sup>; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 – 216 x 356 mm)

500-sheet universal paper cassette, 60 – 120 g/m<sup>2</sup>; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 – 216 x 356 mm)

Max. input capacity incl. options: 2,600 sheets

##### Duplex functionality as standard:

Double-sided printing: A4, A5, B5, Letter, Legal, Custom (140 x 210 mm – 216 x 356 mm), 60 – 120 g/m<sup>2</sup>

**Output capacity:** 500-sheet-face-down with paper full sensor and optional 250-sheet-face-up with PT-320

#### CONTROLLER

**CPU:** 1.2 GHz

**Memory:** 512 MB RAM, max. 2,560 MB RAM

**Standard interface:** USB 2.0 (Hi-Speed), 2 USB Host Interfaces, Gigabit Ethernet (10/100/1000BaseT), Slot for optional internal print server or SSD hard disc, Slot for optional SD/SDHC-Card

**Controller language:** PRESCRIBE IIe

**Emulations:** PCL6 (PCL5c/PCL-XL), PostScript® 3 (KPDL 3), XPS Direct Print, PDF Direct Print 1.7, IBM Proprinter X24E, Epson LQ-850 with automatic emulation sensing

**Operating systems:** All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX as well as other operating systems on request

**Fonts/Barcodes:** 93 scalable fonts for PCL/PostScript®, 8 fonts for Windows Vista®, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

**Security features:** IPSec, HTTPS, SNMPv3, IPPS, Encrypted PDF Direct Print, Private Print, Secure printing via SSL, POP over SSL, SMTP over SSL, Access control via 100 integrated department codes. Data Security Kit (E) protects data on the optional SSD.

**Mobile printing support:** KYOCERA Mobile Print app for iOS and Android; Mopria, Google Cloud Print

#### CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752

**TK-3190 Toner-Kit:** Microfine toner for 25,000 pages A4

**TK-3170 Toner-Kit:** Microfine toner for 15,500 pages A4

**TK-3160 Toner-Kit:** Microfine toner for 12,500 pages A4

Capacity of starter toner is 10,000 pages A4.

#### Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

#### USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

#### Application-based Profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed with activated duplex mode as standard, thus leading to a reduced paper consumption.

#### OPTIONS

**PF-320 Paper feeder (max. 4 units):** Max. 500 sheets; 60 – 120 g/m<sup>2</sup>; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

**PF-3100 Bulk paper feeder and PB-325 Printer base:** Max. 2,000 sheet, 60 – 220 g/m<sup>2</sup>, not to be combined with PF-320

**CB-360 Cabinet:** Wooden desk with storage capacity, Approx. 38cm x 41cm x 50cm (WxDxH)

**CB-365 Cabinet:** Wooden desk with storage capacity, Approx. 38cm x 41cm x 35cm (WxDxH)

**PT-320 Paper tray:** 250-sheet-face-up output tray

##### Memory upgrade:

**MD3-1024:** 1.024 MB, **MDDR3-2GB:** 2.048 MB

**HD-6 SSD hard disc:** 32 GB for easy document management

**HD-7 SSD hard disc:** 128 GB for easy document management

**Data security kit (E):** Encrypts data stored on optional SSD

**USB IC Card Reader + Card Authentication Kit (B):** Support for various authentication keys available

**UG-33:** ThinPrint support

##### Optional interface:

**IB-36:** Wireless LAN (802.11b/g/n) with Wi-Fi Direct

**IB-50:** Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)

**IB-51:** Wireless LAN (802.11b/g/n)

**IB-32B:** Parallel IEEE1284 interface kit


#### MODEL VARIATIONS

**ECOSYS P3055DN/KL3:** ECOSYS P3055DN incl. warranty extension KYOLife 3 years

#### WARRANTY

1-year warranty\*\* as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 500,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

**KYOLIFE** The up to 5-year on-site warranty extension for printer and options.



KYOCERA Document Solutions Europe B.V. – Branch Office Germany  
Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany  
Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100  
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri  
Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

\* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

\*\* Depending on the country