

Epson **7450** Stylus Pro

Fast, consistent, high-quality A1/24" production printer

The ideal printer to bring professional printing in-house. Combines high speed and reliability for improved productivity and throughput. Includes Epson UltraChrome[™] ink for truly outstanding, consistent colour.

This printer satisfies the exacting demands of graphics or point-of-sale printing and even mask making*. It's versatile and consistently professional, with Epson UltraChrome ink to ensure superb, repeatable, long-lasting quality.

The 4-colour inks are fed through a full 8-channel, double-nozzle ink supply, for both speed and overnight reliability. And because the printer's so easy to use, you don't need to be a specialist to get expert results.

Produce superb results in-house – speed, reliability and consistent quality with total control

Colour consistency – Epson UltraChrome ink produces vivid, long lasting results time after time **4-colour inks, 8 channels** – high speed, cost-effective ink system with two nozzles per colour

Skilled operator not needed – enjoy the user friendliness of our consumer range in our professional printers

Improve your productivity – high print speeds for fast results and excellent reliability for overnight printing

Central control – optional software enables remote printing from one location to several printers

Compatibility across the Epson range – achieve consistent results with different printers

Key benefits:

- Fast, reliable, true in-house A1/24" production printer
- Consistent quality from 4-colour Epson UltraChrome ink
- Ideal for graphics, point-of-sale and precise line drawings
- Combines high productivity and throughput with ease and value

Epson Stylus Pro 7450			
Size	24" (A1)		
Print technology	Epson Micro Piezo™ drop-on-demand inkjet technology		
	Epson Variable-sized Droplet Technology and 3.5 pl Epson Ultra Micro Dot™		
	Print head configuration: 180	nozzles x 8 colours	
lnk system	Dual 4 colours pigmented ink (C, M, Y, Matte K) with CSIC with 8 slots		
Resolution	1440 x 720 dpi Epson Variable-sized Droplet Technology		
Memory	64MB		
Speed (max. 360 x 360 dpi)	Up to 23.3 m² / Hr (A1 / Plain paper / Draft mode)		
Driver Interfaces	Microsoft [®] Windows 2000 / XP, Windows Vista, MAC OS [®] X 10.x.x Standard: USB 2.0 (Compatible with 1.1), Ethernet 10 / 100Mb		
Roll dimensions	Core diameter 2" or 3"		
	Max. outside diameter ¢150 mm		
Paper handling			
Roll media	Single roll (1 roll < 150 mm / outside diameter)		
	Media width 203.2 mm - 610 mm (8" - 24")		
	Minimum media length 279 mm		
Cut sheet	Manual insertion feeder for media up to 1.5 mm		
	Media width size A4 / LTR – A1+ / 24" (210 mm – 610 mm)		
Print margins	Media thickness 0.08 mm - 1.50 mm		
Roll media	3 modes available; mode 1: 3 mm on all edges (top, sides, bottom);		
Non media	mode 2: 15 mm (top and bottom), 3 mm (sides);		
	mode 3: 15 mm (top, sides, bottom)		
Sheet media	2 modes available; mode 1: 3 mm (top, sides, bottom);		
	mode 2: 3 mm (top and sides) 14 mm (bottom)		
Ink cartridges	110 and 220 ml ink capacity, single size packaging		
	Matha I.I. I.	110 ml	220 ml
	Matte black Cyan	C13T611800 C13T611200	C13T612800 C13T612200
	Magenta	C13T611300	C13T612300
	Yellow	C13T611400	C13T612400
Photo black for screenprint			
application	4C Photo Black		C13T612100 (only applicable to special version)
Lightfastness	Up to 75 years for colour prints		
General			
Dimensions (WxDxH)	1178 x 501 x 560 mm		
	1178 x 745 x 1180 mm (with stand)		
Weight	Approx. 48.9 kg (without ink and media) Stand approx. 10.5 kg		
Noise level	Approx. 50dB		
Voltage / Current / Frequency Power consumption	100 – 120 V version, 220 – 240 V version Printing: 55 W or less		
Power consumption	Standby: 6 W or less		
	PowerOff: 1 W or less		
Warranty	1 year on-site repair		
-	Optional extension to 3 years	3	
Options	2 / 3 inch dual roll feed spind	lle (High tension)	C12C811155
	Maintenance tank (x2)		C12C890191



Telephone: 08702 416900 (UK) 1 800 409132 (Republic of Ireland) E-mail: info@epson.co.uk www.epson.co.uk www.epson.ie Fax: +44 (0) 8702 413093

